

20M Rated Doors - Neutral Pressure

Parameters	Minimum	Maximum
Door Width:	1'2-3/4"	4'0"
Paired Opening Width:	2'-5-1/2"	8'0"
Door Height:	--	9'0"
Door Thickness:	1-3/4"	2-1/4"
Stiles, Rails & Mullions:		
Stile Width:	4-3/8"	--
Bottom Rail Width:	4-9/16"	--
Mullion Width:	3"	--
Door Panels:		
Width:	6"	39-1/2"
Height:	6"	81-1/2"
Thickness - Raised:	1-1/8"	--
Thickness - Flat:	3/4"	--
Lites:		
Width:	6"	32"
Height:	6"	81"
Area Per Lite	36"	2,592"
Area Per door	--	2,592"
Lite/Lock Spacing:	1-1/2"	--
Moulding:	1/2"	--
Warranty:	Lifetime Interior	

**All lites must be listed and glazed at the factory.*

20M Rated Doors - Positive Pressure

Parameters	Minimum	Maximum
Door Width:	1'4"	4'0"
Paired Opening Width:	2'8"	8'0"
Door Height:	--	9'0"
Door Thickness:	1-3/4"	2-1/4"
Stiles, Rails & Mullions:		
Stile Width:	5"	--
Bottom Rail Width:	9-1/2"	--
Mullion Width:	3"	--
Door Panels:		
Width:	6"	39-1/2"
Height:	6"	81-1/2"
Thickness - Raised:	1-1/8"	--
Thickness - Flat:	3/4"	--
Lites:		
Width:	8"	32"
Height:	10"	81"
Area Per Lite	80"	2,592"
Area Per door	--	2,592"
Lite/Lock Spacing:	1-1/2"	--
Moulding:	1/2"	1/2"
Warranty:	Lifetime Interior	

**All lites must be listed and glazed at the factory.*

45M/60M Rated Doors - Positive Pressure

Parameters	Minimum	Maximum
Door Width:	1'4"	3'6"
Paired Opening Width:	2'8"	7'0"
Door Height:	--	8'0"
Door Thickness:	1-3/4"	1-3/4"
Stiles, Rails & Mullions:		
Stile Width:	5"	--
Bottom Rail Width:	5"	--
Mullion Width:	3"	--
Door Panels:		
Width:	6"	32"
Height:	6"	81"
Thickness - Raised:	1-5/8"	--
Thickness - Flat:	7/8"	--
Lites:	Not Allowed	
Moulding:	3/8"	--
Temp. Rise at 30 minutes:	250 degrees Fahrenheit	
Warranty:	2 Years, Interior Only	

90M Rated Doors - Positive Pressure

Parameters	Minimum	Maximum
Door Width:	1'4"	3'6"
Paired Opening Width:	2'8"	7'0"
Door Height:	--	8'0"
Door Thickness:	1-3/4"	2-1/4"
Stiles, Rails & Mullions:		
Stile Width:	5"	--
Bottom Rail Width:	10"	--
Mullion Width:	3"	--
Door Panels:		
Width:	6"	32"
Height:	6"	81"
Thickness - Raised:	1-7/8"	--
Thickness - Flat:	1-1/8"	--
Lites:	Not Allowed	
Moulding:	3/8"	--
Temp. Rise at 30 minutes:	250 degrees Fahrenheit	
Warranty:	2 Years, Interior Only	